




TECHNICAL DATA SHEET

Issue Date: June 2007

Anchor Diamond®

		DIAMOND BLOCK	CORNER BLOCK	CAP BLOCK
Standard Block Range				
			Partial units may be required to maintain running bond.	
PHYSICAL PROPERTIES				
Length	mm	435	200	450 - Long Side 330 - Short Side
Height	mm	150	150	75
Depth	mm	300	300	250
Block Coverage		0.065 m ² /block 15.4 blocks/m ²	0.030 m ² /block (Short Face) 0.045 m ² /block (Long Face)	0.390 linear m/block ₍₁₎ 2.56 blocks/m ₍₁₎
Approximate mass per block	kg	29	14.5	16.5
Set Back / Face Angle		28mm (10.6°)	28mm (10.6°)	N/A
Minimum Inside Radius (Back of block on base course)	m	2.7	-	-
Minimum Outside Radius (Back of block on top course)	m	0.9	-	-
DELIVERY INFORMATION				
Blocks per Pallet		54	54 left & 54 right	60
GENERAL PROPERTIES				
Tolerance on all dimensions	mm	±1		
Compressive Strength ⁽²⁾	N/mm ²	21		
Face Texture		Textured		
Aggregate		5mm Limestone, Mill Fines, Concrete Sand		
Face Geometry		Stretcher		

Colours available

*Basalt, *Bracken, Brindle, Cathedral, Cotswold Buff

(1) Refers to the average coverage length per block for straight walls

*Colours made to order

Manufacturing & Sales Support by:

Acheson — GLOVER

UK Sales - BIRMINGHAM
T: 0121 747 0202 F: 0121 747 2913
E: uksales@acheson-glover.com

Sales Headquarters - DUNGANNON:
T: 028 8778 4208 F: 028 8778 4805
E: sales@acheson-glover.com

Headquarters - FIVEMILETOWN:
T: 028 8952 1275 F: 028 8952 1866
E: fmit@acheson-glover.com

www.acheson-glover.com

Engineering & Sole Distribution by:

MACCAFERRI

OXFORD:
T: 01865 770555 F: 01865 774550
E: oxford@maccaferri.co.uk

PERTH:
T: 01738 621317 F: 01738 442283
E: perth@maccaferri.co.uk

BELFAST:
T: 028 9026 2830 F: 028 9026 2849
E: belfast@maccaferri.co.uk

www.maccaferri.co.uk

Approved lifting device for Vertica® system



www.anchorwall.eu