





TECHNICAL DATA SHEET

Issue Date: June 2007

Anchor Landmark



		FULL HEIGHT	TAPERED FULL	HALF HEIGHT	FOUNDATION
Manufactured under BBA Roads & Bridges Specifications					
PHYSICAL PROPERTIES					
Length	mm	200	200	200	200
Height	mm	380	380	190	190
Depth	mm	300/320 ⁽¹⁾	300/320 ⁽¹⁾	300 or 310	300
Block Coverage		0.076 m ² /block 13.2 blocks/m ²	0.076 m ² /block 13.2 blocks/m ²	0.038 m ² /block 26.3 blocks/m ²	0.019 linear m/block
Approximate mass per block	kg	39	37	23	22
Set Back / Face Angle		25mm (3.8°)	25mm (3.8°)	12mm (3.8°)	-
Minimum Inside Radius (Back of block on base course)	m	2.10	2.10	2.10	
Minimum Outside Radius (Back of block on top course)	m	2.45	2.45	2.45	
DELIVERY INFORMATION					
Blocks per Pallet		45	45	36	60
GENERAL PROPERTIES					
Tolerance on all dimensions	mm	±1			
Compressive Strength ⁽²⁾	N/mm ²	40			
Face Texture		Textured			
Aggregate		5mm Limestone, Mill Fines, Concrete Sand			
Face Geometry		Soldier			
BBA Approval		Anchor Landmark Wall Systems is BBA Roads & Bridges certified for use with Engagrid PRO geogrids. Agrément Certificate No. 04/R138			

Colours available

Brindle, Cathedral, Cotswold Buff

(1) Refers to the average coverage length per block for straight walls

Manufacturing & Sales Support by:

Acheson — GLOVER

UK Sales - BIRMINGHAM
T: 0121 747 0202 F: 0121 747 2913
E: uksales@acheson-glover.com

Sales Headquarters - DUNGANNON:
T: 028 8778 4208 F: 028 8778 4805
E: sales@acheson-glover.com

Headquarters - FIVEMILETOWN:
T: 028 8952 1275 F: 028 8952 1866
E: fmi@acheson-glover.com

www.acheson-glover.com

Engineering & Sole Distribution by:

MACCAFERRI

OXFORD:
T: 01865 770555 F: 01865 774550
E: oxford@maccaferri.co.uk

PERTH:
T: 01738 621317 F: 01738 442283
E: perth@maccaferri.co.uk

BELFAST:
T: 028 9026 2830 F: 028 9026 2849
E: belfast@maccaferri.co.uk

www.maccaferri.co.uk

Approved lifting device for Landmark system



www.anchorwall.eu