





TECHNICAL DATA SHEET

Issue Date: June 2007

Anchor Vertica®



		VERTICA BLOCK	END BLOCK	CORNER BLOCK	CAP BLOCK
Manufactured under BBA Specifications					
PHYSICAL PROPERTIES					
Length	mm	457	230	457	438 - Long Side 303 - Short Side
Height	mm	200	200	200	100
Depth	mm	280	280	228	254
Block Coverage		0.091 m ² /block 10.9 blocks/m ²	N/A	0.046 m ² /block (Short Face) 0.091 m ² /block (Long Face)	0.37 linear m/block ₍₁₎ 2.70 blocks/m ₍₁₎
Approximate mass per block	kg	39	20	43	20
Set Back / Face Angle		25.4mm (7.3°)	N/A	25.4mm (7.3°)	N/A
Minimum Inside Radius (Back of block on base course)	m	2.4	N/A	-	-
Minimum Outside Radius (Back of block on top course)	m	1.8	N/A	-	-
DELIVERY INFORMATION					
Blocks per Pallet		45	Made to order	40	48
GENERAL PROPERTIES					
Tolerance on all dimensions	mm	±1			
Compressive Strength⁽²⁾	N/mm²	30			
Face Texture		Textured			
Aggregate		5mm Limestone, Mill Fines, Concrete Sand			
Face Geometry		Stretcher			
BBA Approval		Anchor Vertica® Wall Systems is BBA certified for use with ParaGrid™ geogrids. Agrément Certificate No. 03/ 4032			

Colours available

*Basalt, *Bracken, Brindle, Cathedral, Cotswold Buff

(1) Refers to the average coverage length per block for straight walls

*Colours made to order

Manufacturing & Sales Support by:

Acheson — GLOVER

UK Sales - BIRMINGHAM
T: 0121 747 0202 F: 0121 747 2913
E: uksales@acheson-glover.com

Sales Headquarters - DUNGANNON:
T: 028 8778 4208 F: 028 8778 4805
E: sales@acheson-glover.com

Headquarters - FIVEMILETOWN:
T: 028 8952 1275 F: 028 8952 1866
E: fmt@acheson-glover.com

www.acheson-glover.com

Engineering & Sole Distribution by:

MACCAFERRI

OXFORD:
T: 01865 770555 F: 01865 774550
E: oxford@maccaferri.co.uk

PERTH:
T: 01738 621317 F: 01738 442283
E: perth@maccaferri.co.uk

BELFAST:
T: 028 9026 2830 F: 028 9026 2849
E: belfast@maccaferri.co.uk

www.maccaferri.co.uk

Approved lifting device for Vertica® system



www.anchorwall.eu