



MACMAT-R PVC GALFAN GALVANISED 6 / 2.2

SPECIFICATIONS

PROPERTIES

Type	Double twist hexagonal woven steel wire mesh onto which a 3D geomat matrix is extruded	 <p>D = 60mm (Nominal)</p>
Mesh Type	6 x 8	
Mesh Wire	2.2mm diameter (BS EN 10218-2 & BS EN 10223-3)	
Selvedge Wire	2.7mm diameter (BS EN 10218-2 & BS EN 10223-3)	
Corrosion Protection	Galfan galvanised (95% Zinc + 5% Aluminium Alloy + Mischmetals) coated to BS EN 10244-2 Class A (230 g/m ²) with an extruded grey PVC coating of mean wall thickness of 0.5mm	
Geomat Type	A three dimensional geomat of entangled polypropylene monofilaments, heat bonded at contact points, 10mm thick with a void space of 90%.	
Roll Size / Weight	2m x 25m (Roll Weight = 90 kg (Nominal))	
Jointing	All joints and connections shall be formed with continuous 2.2mm PVC Galfan coated lacing wire and/ or high tensile 3mm diameter Stainless Steel 'C' rings.	
BBA Approval	Maccaferri hexagonal wire mesh is BBA certified for up to 120 years design life. Agrément Certificate No. 95/3141	



All units are supplied with sufficient lacing wire for standard installation.
Maccaferri reserves the right to alter specifications of its products without notice.
Please contact us for the most up to date specifications.

Maccaferri Ltd - Head Office

7600 The Quorum,
Oxford Business Park, North,
Garsington Road, Oxford, OX4 2JZ
Tel: 01865 770555
Fax: 01865 774550
Email: oxford@maccaferri.co.uk
Web: www.maccaferri.co.uk

Area offices

Perth:
T: 01738 621317 F: 01738 442283 E: perth@maccaferri.co.uk
Belfast:
T: 028 9026 2830 F: 028 9026 2849 E: belfast@maccaferri.co.uk
Dublin:
T: 01 885 1662 F: 01 885 1601 E: dublin@maccaferri.ie
Web: www.maccaferri.ie



Oxford, Perth, Belfast